TÜ puhverserveri seadistamine Linuxis

Siit juhendist leiad juhised Tartu Ülikoolis kasutusel oleva puhverserveri seadistamise kohta Linux seadmes.

In English

Puhverserveri (ingl Proxy) kasutamiseks tuleb seadistada operatsioonisüsteemi ja veebibrauseri seadistused järgnevalt:

- 1. Seadista puhverserer enda operatsioonisüsteemi põhiselt.
- 2. Seadista puhverserver enda veebilehitseja põhiselt.

Puhverserveri aktiveerimine

- 1. Ava puhverserveri seaded (9 täppi) kasutades Linux otsingut Settings blocked URL
- 2. Vali Network > Network Proxy > Hammasratas

Q	Settings	=	Network –	×
(î•	Wi-Fi			
۲				
*	Bluetooth		Not set up	
Ģ	Background			
P	Appearance		Network Proxy Off	
Ţ	Notifications			
Q	Search		ון נ	
Ð	Multitasking		2	
	Applications	\rangle		
₿	Privacy	>		
	Online Accounts			
<°	Sharing			
л	Sound			
٩	Power			
P	Displays			
O	Mouse & Touchpad			
	Keyboard			_



a. Automatic

- b. Sisesta Configuation URL lahtrisse "http://www.ut.ee/utlib.pac".
 c. Pane ristist kinni

	Network Proxy	×
O Automatic	⊐1	
🔿 Manual	-	
 Disabled 		
Configuration URL	http://www.ut.ee/utlit	2
L. L	ttp://www.ut.ee/utlib.pac	

1. **NB!** Enne Mozilla Firefox proxy seadistamist veendu, et seadistasid operatsioonisüsteemi puhverserveri seaded. Vali Firefoxi menüüst **Options** (kolm paralleelset joont ekraani üleval paremal servar) ja seejärel **Settings**.

\$	${\times}$	×.	\gg	பி	≡	
Sync and save data				Sign I	•∆	
New tab				Ctr	1+1	
New window				Ctrl+N		
New private window	N		Ctrl	+Shift	:+P	
Bookmarks					>	
History					>	
Downloads			Ctrl	+Shift	:+Y	
Passwords						
Add-ons and theme	s		Ctrl	+Shift	:+A	
Print				Ctr	l+P	
Save page as				Ctr	l+S	
Find in page	2			Ctr	l+F	
Zoom	4	- 1	100%	+	2	
Settings						
More tools					>	
Help					>	
Quit				Ctrl	+Q	

-					
õpsa külgriba nupul Gen	eral ja seejärel kerige täiesti alla. Vajuta sektsioonis "Network Settings" nupule "Settings"				
ණි General	Use recommended performance settings Learn more				
Home	These settings are tailored to your computer's hardware and operating system.				
Q Search					
	Browsing				
	Use autoscrolling				
🗘 Sync	✓ Use s <u>m</u> ooth scrolling				
m More from Mozilla	Always show scrollbars				
	Always use the cursor keys to navigate within pages				
	Search for te <u>x</u> t when you start typing				
	Enable picture-in-picture video controls Learn more				
	🗹 Control media via keyboard, headset, or virtual interface 🛛 Learn more				
	Recommend extensions as you browse Learn more				
	Recommend <u>f</u> eatures as you browse Learn more				
	Network Settings				
술 Extensions & Themes	Configure how Firefox connects to the internet. Learn more 2 C				
anenud dialoogiaknas v	ali "Automatic proxy configuration URL" ja sisesta dialoogikasti väärtuseks http://www.ut.ee/utl				
O <u>A</u> utomatic proxy con	figuration URL				
http://www.ut.ee/u	utlib.pad				
<u>N</u> o proxy for					
Example: .mozilla.org, .n	et.nz, 192.168.1.0/24				
Connections to localhos	t, 127.0.0.1/8, and ::1 are never proxied.				
Do not prompt for au	uthent <u>i</u> cation if password is saved				

4. Vajuta **OK** ja sulge eelistuste dialoog akna nurgast.

1. Peale proxy seadistuste läbi viimist kasutab Google Chrome automaatselt süsteemi seadistusi.

Puhverserveri deaktiveerimine

- 1. Ava puhverserveri seaded (9 täppi) kasutades Linux otsingut Settings blocked URL
- 2. Vali Network > Network Proxy > Hammasratas



3. Vali Disabled.

1. Ülikooli puhverserveri kasutamise lõpetamiseks ava sama dialoog ja vali "No proxy".

Connection Settings					
<u>Configure Prox</u> y Access to the Internet					
ΟΝο ρгοχ <u>γ</u>					
Auto-detect proxy settings for this net <u>w</u> ork					
○ <u>U</u> se system proxy settings					
<u>M</u> anual proxy configuration					

2. Vajuta OK ja sulge eelistuste dialoog akna nurgast.

1. Google Chrome kasutab operatsioonisüsteemi (Linux) puhverserveri seadistusi. Dekativeerimiseks tuleb Linux puhverserver deaktiveerida.